



US007854423B2

(12) **United States Patent**
Hoffend, Jr.

(10) **Patent No.:** **US 7,854,423 B2**
(45) **Date of Patent:** **Dec. 21, 2010**

(54) **MODULAR LIFT ASSEMBLY**

(75) Inventor: **Donald A. Hoffend, Jr.**, Pittsford, NY
(US)

(73) Assignee: **Daktronics Hoist, Inc.**, Brookings, SD
(US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/189,002**

(22) Filed: **Aug. 8, 2008**

(65) **Prior Publication Data**

US 2009/0045381 A1 Feb. 19, 2009

Related U.S. Application Data

(60) Continuation of application No. 11/185,997, filed on Jul. 20, 2005, now abandoned, which is a division of application No. 10/717,886, filed on Nov. 20, 2003, now abandoned, which is a continuation-in-part of application No. 10/274,725, filed on Oct. 19, 2002, now Pat. No. 6,988,716, which is a continuation-in-part of application No. 10/273,285, filed on Oct. 17, 2002, now Pat. No. 6,691,986, which is a division of application No. 09/627,537, filed on Jul. 28, 2000, now Pat. No. 6,634,622.

(51) **Int. Cl.**
B66D 3/08 (2006.01)

(52) **U.S. Cl.** **254/331**; 254/378; 254/388

(58) **Field of Classification Search** 254/278,
254/286, 338, 331, 329, 378, 388, 389; 160/331,
160/344, 143

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

977,499 A 12/1910 Bailey
977,500 A 12/1910 Bailey

1,263,628 A	4/1918	Vallen
1,340,066 A	5/1920	Lemle
1,473,336 A	11/1923	Connelly
1,821,563 A	9/1931	Mitchell et al.
2,357,462 A	9/1944	Ferguson
2,649,279 A	8/1953	Jones et al.
2,775,324 A	12/1956	Tate
2,811,262 A	10/1957	Schaitberger
2,912,180 A	11/1959	Lindberg
3,313,070 A	4/1967	Elofson
3,526,388 A	9/1970	Geiger et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 255522 A1 4/1988

(Continued)

OTHER PUBLICATIONS

"Cyclorama Batten Systems", *Regional Performing Arts Center*, Philadelphia, PA, (Dec. 15, 1999), 3 pgs.


Primary Examiner—Emmanuel M Marcelo

(74) *Attorney, Agent, or Firm*—Schwegman, Lundberg & Woessner, P.A.

(57) **ABSTRACT**


A lift assembly having a drum rotatably mounted to a frame and linearly translatable with respect to one or more portions of the frame. A plurality of head blocks can be connected to the frame along a helical mounting path, wherein linear translation of the drum during takeoff or take-up can maintain a predetermined fleet angle between a take off point from the drum and the head block.


20 Claims, 8 Drawing Sheets




U.S. PATENT DOCUMENTS

3,572,703 A	3/1971	Greene	6,023,862 A	2/2000	Sirjola
4,046,235 A	9/1977	Shutt	6,080,981 A	6/2000	Payne
4,062,519 A	12/1977	Jacobs	6,118,652 A	9/2000	Casby et al.
4,156,521 A	5/1979	Harman	6,155,538 A	12/2000	Winter
4,170,308 A	10/1979	Rogers	6,299,139 B1	10/2001	Kazerooni
4,251,059 A	2/1981	Fougea	6,364,062 B1	4/2002	Ericson et al.
4,324,386 A *	4/1982	Gagnon et al. 254/288	6,517,054 B2	2/2003	Samejima
4,438,903 A	3/1984	Gagnon et al.	6,520,485 B1	2/2003	Soot
4,446,587 A	5/1984	Jump	6,554,252 B2	4/2003	Kazerooni et al.
4,532,739 A	8/1985	Cooper	6,615,564 B2	9/2003	Luttrario et al.
4,606,527 A	8/1986	Ziller et al.	6,634,621 B2	10/2003	Keith
4,624,386 A	11/1986	Grigorenko et al.	6,634,622 B1 *	10/2003	Hoffend, Jr. 254/394
4,662,628 A	5/1987	Chatenay epouse Compagnone	6,691,986 B2	2/2004	Hoffend, Jr.
4,772,923 A	9/1988	Lein	6,729,605 B2	5/2004	Brackman et al.
4,802,787 A	2/1989	Bays	6,802,170 B2	10/2004	Davis
4,905,849 A	3/1990	Coull	6,807,790 B2	10/2004	Strickland et al.
5,003,732 A	4/1991	Quinnell	6,889,958 B2	5/2005	Hoffend, Jr.
5,031,574 A	7/1991	McDowell	6,988,716 B2	1/2006	Hoffend, Jr.
5,074,528 A	12/1991	Long, Jr.	6,997,442 B2	2/2006	Hoffend, Jr.
5,106,057 A	4/1992	Feller et al.	7,210,670 B2 *	5/2007	Franks 254/294
5,141,085 A	8/1992	McCormick	7,264,227 B2 *	9/2007	Miller et al. 254/331
5,190,250 A	3/1993	DeLong et al.	7,284,744 B1 *	10/2007	Lerchenmueller et al. ... 254/278
5,263,660 A	11/1993	Brozik	7,562,863 B2 *	7/2009	Kochan et al. 254/394
5,351,937 A	10/1994	Nishi et al.	2003/0030045 A1	2/2003	Hoffend, Jr.
5,361,565 A	11/1994	Bayer	2003/0111652 A1	6/2003	Hoffend, Jr.
5,492,306 A	2/1996	Zaguroli, Jr.	2004/0084665 A1	5/2004	Hoffend, Jr.
5,553,832 A	9/1996	Zaguroli, Jr.	2004/0098944 A1	5/2004	Hoffend, Jr.
5,555,695 A	9/1996	Patsy, Jr.	2004/0099852 A1	5/2004	Hoffend, Jr.
5,570,872 A	11/1996	Inoue et al.	2004/0183060 A1	9/2004	Hoffend, Jr.
5,586,751 A	12/1996	Ueno et al.	2005/0247919 A1	11/2005	Hoffend, Jr.
5,593,138 A	1/1997	Zaguroli, Jr.	2006/0169662 A1	8/2006	Hoffend, Jr.
5,661,945 A	9/1997	Henriksson et al.	FOREIGN PATENT DOCUMENTS		
5,662,311 A	9/1997	Waedekin et al.	DE	3737612 A1	6/1989
5,678,805 A	10/1997	Moser et al.	DE	4204153 A1	8/1993
5,711,713 A	1/1998	Krueger	DE	29912572 U1	9/1999
5,772,360 A	6/1998	Wood, II	EP	0540136 A1	5/1993
5,794,400 A	8/1998	Fisher et al.	EP	0639684 A1	2/1995
5,848,781 A	12/1998	Kulhavy et al.	EP	0778239 A1	6/1997
5,865,426 A	2/1999	Kazerooni	FR	2689415 A1	10/1993
6,007,054 A	12/1999	Kobayasi et al.	* cited by examiner		










Fig. 4A

Fig. 4B




Fig. 5




Fig. 6




Fig. 8




Fig. 11




Fig. 7




Fig. 9




Fig. 10




Fig. 12




Fig. 13

1

MODULAR LIFT ASSEMBLY**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 11/185,997 filed Jul. 20, 2005 now abandoned, which is a divisional of U.S. patent application Ser. No. 10/717,886 filed Nov. 20, 2003, now abandoned, which is a continuation-in-part of U.S. patent application Ser. No. 10/274,725 filed Oct. 19, 2002, now U.S. Pat. No. 6,988,716, which is a continuation-in-part of U.S. patent application Ser. No. 10/273,285 filed Oct. 17, 2002, now U.S. Pat. No. 6,691,986, which is a divisional of U.S. patent application Ser. No. 09/627,537 filed Jul. 28, 2000, now U.S. Pat. No. 6,634,622, the specifications of which are herein incorporated by reference in their entirety.

This application is also related to U.S. application Ser. No. 10/690,132 filed Oct. 21, 2003, now U.S. Pat. No. 6,889,958, U.S. application Ser. No. 10/813,424 filed Mar. 29, 2004, now U.S. Pat. No. 6,997,442, U.S. application Ser. No. 11/463,823 filed Aug. 10, 2006, now U.S. Pat. No. 7,293,762, and U.S. application Ser. No. 11/325,401 filed Jan. 4, 2006, now U.S. Pat. No. 7,258,325, the specifications of which are herein incorporated by reference in their entirety.

TECHNICAL FIELD

This patent document pertains generally to lift and hoist mechanisms. More particularly, but not by way of limitation, this patent document pertains to a lift assembly that can be employed for raising and lowering a load in theatrical and staging environments, wherein the lift assembly is a modular self contained unit that can be readily installed in a wide variety of building configurations.

BACKGROUND

Performance venues such as theaters, arenas, concert halls, auditoriums, schools, clubs, convention centers and television studios employ battens or trusses to suspend lighting, scenery, drapery and other equipment which is moved relative to a stage or floor. These battens usually include pipe or joined pipe sections that form a desired length of the batten. The battens can be 50 feet or more in length. To support heavy loads or where suspension points are spaced 15-30 feet apart, the battens may be fabricated in either ladder, triangular or box truss configurations.

Battens often need to be lowered for exchanging and servicing the suspended equipment. To reduce the power necessary to raise and lower the battens, the battens are often counterweighted. The counterweights reduce the effective weight of the battens and any associated loads.

A typical counterweight system represents a significant cost. The creation of T-bar wall 70 feet to 80 feet in height and 30 feet deep may require over three weeks. Even after installation of the T-bar wall, head block beams, loading bridges, index lights and hoist systems must be integrated. Therefore, a substantial cost is incurred in the mere installation of a counterweight system. The total installation time may range from 6 to 12 weeks.

A number of elevating or hoisting systems are available for supporting, raising and lowering battens. One of the most common and least expensive batten elevating systems is a counterweighted carriage which includes a moveable counterweight for counterbalancing the batten and equipment supported on the batten.

2

Another common elevating or hoisting system employs a winch to raise or lower the battens. Usually hand or electric operated winches are used to raise or lower the battens. Occasionally in expensive operations, a hydraulic or pneumatic motorized winch or cylinder device is used to raise and lower the batten.

Many elevating systems have one or more locking devices and at least one form of overload limiting device. In a counterweight system, a locking device may include a hand operated rope that is attached to one end of the top of the counterweight arbor (carrying device) and then run over a head block, down to the stage, through a hand rope block for locking the counterweight in place, and then around a floor block and back up to the bottom of the counterweight arbor. The hand rope lock locks the rope when either the load connected to the batten or the counterweight loads are being changed and rebalanced and locks the loads when not moving.

In a sandbag counterweight system, the locking device is merely a rope tied off to a stage mounted pin rail, while the overload limit is regulated by the size of the sandbag. In this rigging design, however, a number of additional bags can be added to the set of rope lines, and thereby exceed the safe limit of suspension ropes and defeat the overload-limiting feature.

Hand operated winches will occasionally free run when heavily loaded and will then dangerously drop the suspended load. Other types of hand winches use a ratchet lock, but again these winches are also susceptible to free running when they are heavily loaded and hand operated.

BRIEF SUMMARY

The present inventor has recognized, among other things, that a need exists for a lift assembly that can replace traditional counterweight systems. The need further exists for a lift assembly that can be readily installed into a variety of building configurations and layouts. A need further exists for a lift assembly having a modular construction to facilitate configuration to any of a variety of installations. A need also exists for a lift assembly that can maintain a predetermined fleet angle during raising or lowering of a load.

The present lift assembly can include a lift frame, a plurality of head blocks connected to the frame, and a drum rotatably connected to the frame about a longitudinal axis of the drum, the drum also being translatable along its longitudinal axis relative to the head blocks to maintain a predetermined fleet angle between the head blocks.

In a further configuration, the present lift assembly can include a bias mechanism such as a torsion spring connected between the frame and the drum for reducing the effective weight of the load or batten and any associated equipment.

The lift assembly employs a modular frame for accommodating a different number of head blocks. The lift assembly can also include a modular drum construction which allows for the ready and economical configuration of the system to accommodate various stage sizes. The lift assembly further contemplates the head blocks connected to the frame to be radially spaced about the axis of drum rotation. In a further configuration, the head blocks can be radially and longitudinally spaced relative to the axis of drum rotation, to lie in a helical or a serpentine path relative to the drum.

The lift assembly further contemplates a load brake for reducing the risks associated with drive or motor failures. In addition, the present lift assembly contemplates a clip assembly for readily engaging the frame with structural beams, which can have any of a variety of dimensions. In addition, a

power/control strip can be provided for supplying the power to a lift assembly as well as control signals.

The present lift assembly can further include one or more loft blocks for guiding the cable from the modular frame to the battens. In a further configuration, the present lift assembly contemplates selective height or trim adjustment for a section of a batten relative to the respective cable. A further configuration of the present lift assembly provides a safety stop for terminating movement of batten upon detection of an obstacle in an intended travel path of the batten.

The present lift assembly provides a turnkey lift assembly having rigging; power and control for the manipulation of battens, without requiring construction of traditional counterweight systems or relying on previously installed counterweight systems.

These and other examples, advantages, and features of the present lift assembly will be set forth in part in following Detailed Description. This Summary is intended to provide an overview of the subject matter of the present patent document. It is not intended to provide an exclusive or exhaustive explanation of the present subject matter. The Detailed Description is included to provide further information about the present patent document.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, like numerals have been used to describe similar components throughout the several views. Like numerals having different letter suffixes have been used to represent different instances of similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments described in the present document.

FIG. 1 is a perspective partial cutaway view of a building having a plurality of structural members to which the lift assembly is connected.

FIG. 2 is an enlarged perspective partial cutaway view of the installed lift assembly.

FIG. 3 is an exploded perspective view of a drive mechanism for the lift assembly.

FIG. 4a is a perspective view of the connection of the drum, drive mechanism and frame for rotation of the drum and translation of the drum and drive mechanism.

FIG. 4b is an enlarged view of a portion of FIG. 4a.

FIG. 5 is a side elevational view of a drum.

FIG. 6 is an end elevational view of a drum.

FIG. 7 is a perspective view of a longitudinal drum segment.

FIG. 8 is a cross-sectional view of a longitudinal drum segment.

FIG. 9 is a perspective partial cut away view of a clip assembly.

FIG. 10 is an exploded perspective view of a loft block.

FIG. 11 is a cross-sectional view of the trim adjustment.

FIG. 12 is a schematic representation of a plurality of frames connected to a building.

FIG. 13 is a schematic of an alternative arrangement of the frame relative to a building.

DETAILED DESCRIPTION

Referring to FIG. 1, the present lift assembly 10 is employed to selectively raise, lower and locate a batten 12 relative to a building or surrounding structure. Preferably, the lift assembly 10 moves a connected batten 12 between a lowered position and a raised position.

Although the term “batten” is used in connection with theatrical and staging environment, including scenery, staging, lighting as well as sound equipment, it is understood the term encompasses any load connectable to a windable cable.

The term “cable” is used herein to encompass any wire, metal, cable, rope, wire rope or any other generally inelastic windable material.

The term “building” is used to encompass a structure or facility to which the lift assembly is connected, such as but not limited to, performance venues, theaters, arenas, concert halls, auditoriums, schools, clubs, educational institutions, stages, convention centers, television studios showrooms and places of religious gathering. Building is also understood to encompass cruise ships which may employ battens.

Referring to FIGS. 1, 2 and 3, the lift assembly 10 can include a frame, at least one head block 80, a drive mechanism 100, a rotatable drum 160 and a corresponding loft block 220.

The lift assembly 10 can be constructed to cooperate with at least one cable 14. Typically, the number of cables is at least four, but may be as many as eight or more. As shown in the figures, a cable path can extend from the drum 160 through a corresponding head block 80 to pass about a loft block 220 and terminate at the batten 12.

Frame:

As shown in FIGS. 1 and 2, the frame 20 can include a rigid skeleton to which the drum 160, the drive mechanism 100 and the head block 80 are attached. According to at least one configuration, the frame 20 can be sized to enclose the drive mechanism 100, the drum 160, a head block 80 and a loft block 220. However, it is understood the frame can include a backbone to which the components are connected.

The frame 20 may be in the form of a grid or a box. The frame 20 can be formed of angle irons, rods, bars, tubing or other structural members. Typically, the frame 20 includes interconnected runners, struts and crossbars 22. The runners, struts and crossbars may be connected by welding, brazing, rivets, bolts or releasable fasteners. The particular configuration of the frame is at least partially dictated by the intended operating environment and anticipated loading. To reduce the weight of the frame 20, a relatively lightweight and strong material such as aluminum is used in various embodiments. However, other materials including, but not limited to, metals, alloys, composites and plastics can be used in response to design parameters. Although the frame 20 is shown in skeleton configuration, it is understood the frame may be enclosed as a box or enclosure having walls to define and enclose an interior space.

In some embodiments, the frame 20 is formed from a plurality of modular sections 24, wherein the sections may be readily interconnected to provide a frame of a desired length. Thus, the frame 20 may accommodate a variety of cables and hence drum lengths.

The frame 20 is constructed to be connectable to the building. The frame 20 can include a fixed coupler and a sliding coupler, wherein the distance between the fixed coupler and the sliding coupler can be varied to accommodate a variety of building spans. Typically connections of the frame 20 to the building include clamps, fasteners, bolts and ties. These connectors may be incorporated into the frame, or are separate components attached during installation of the frame. As set forth herein, adjustable clip assemblies 40 are provided for retaining the frame relative to the building.

The frame 20 also includes or cooperatively engages mounts for the drive mechanism and bearings for the drum. Specifically, the frame can include a pair of rails for supporting the drive mechanism, a translating shaft and a threaded keeper. As set forth in the description of the drive mechanism

5

100, the drive mechanism can be connected to the frame **20** for translation with the drum along the axis of rotation of the drum.

In the first configuration of the frame **20**, the frame has an overall length of approximately 10 feet, a width of approximately 11 inches and a height of approximately 17 inches.

The frame **20** can include a head block mount **30** for locating the head blocks in a fixed position relative to the frame. In some embodiments, the head block mount **30** is a helical mount concentric with the axis of drum rotation. The inclination of the helical mount is at least partially determined by the length of the drum **160**, the size of associated head blocks **80**, the spacing of the installed frame and the number of cables to be drawn from the drum. Thus, the helical head block mount **30** may extend from approximately 5 degrees of the drum to over 180 degrees. The helical mounting allows the head blocks **80** to overlap along the longitudinal axis of drum rotation, without creating interfering cable paths.

Although the helical mount **30** is shown as a continuous curvilinear strut, it is understood a plurality of separate mounts can be employed, wherein the separate mounts are selected to define a helical or a serpentine path about the axis of rotation of the drum **160**.

In a further construction, the head block mounts **30** can be merely radially spaced about the axis of drum rotation at a common longitudinal position along the axis of drum rotation. That is, rather than being disposed along the longitudinal axis of the drum **160**, the head block mounts **30** are located at a fixed longitudinal position of the drum. However, it has been found that the width of the frame **20** can be reduced by radially and longitudinally displacing the head blocks **80** along a serpentine path about the axis of drum rotation, wherein the head blocks lie within approximately 100 degrees, such as 90 degrees of each other.

As shown in FIGS. **1** and **2**, in the seven-cable configuration, the lift assembly **10** includes two internal and five external lift blocks **220**. The internal lift blocks **220** are located within the frame **20** and the external lift blocks **220** are operably mounted outside the frame, as seen in FIG. **1**. However, the lift assembly **10** can be configured to locate a plurality of external lift blocks **220** from each end of the frame. That is, two or more lift blocks **220** may be spaced from one end of the frame **20** and two or more lift blocks may be spaced from the remaining end of the frame.

In addition, depending upon the configuration of the lift assembly **10**, the number of internal lift blocks **220** can range from none to one, two, three or more.

Hoisting Adapter:

In addition, the frame may include a hoisting adapter **26** or mounts for releasably engaging the hoisting adapter. It is anticipated a plurality of hoisting adapters can be employed, as at least partially dictated by the size of the frame **20** and the configuration of the building. The hoisting adapter **26** can include a sheave **28**, such as a lift block connected to spaced apart locations of the frame. The hoisting adapter **26** can also include a clip assembly **40** for releasably engaging a beam of the building. The hoisting adapter **26** can be selected so that the frame may be hoisted to an operable location and connected to the building by additional clip assemblies **40**.

Head Blocks:

A plurality of head blocks **80** can be connected to the head block mount **30**. The number of head blocks corresponds to the number of cables **14** to be controlled by the lift assembly **10**. The head blocks **80** provide a guide surface about which the cable path changes direction from the drum **160** to a generally horizontal direction. The guide surface may be in the form of sliding surface or a moving surface that moves

6

corresponding to travel of the cable. Each head block **80** draws cable **14** from a corresponding winding section along a tangent to the drum **160**. The angle between the head block **80** and the respective cable take off point from the drum **160** may be repeated by each of the head blocks **80** relative to the drum.

As the head blocks **80** are mounted to the head block mount **30**, such as the helical mount, the head blocks can overlap along the axis of drum rotation. The overlap allows for size reduction in the lift assembly **10**. That is, a helical mounting of the head blocks **80** allows the head blocks to overlap radially as well as longitudinally relative to the axis of drum rotation. By overlapping radially, the plurality of head blocks **80** can be operably located within a portion of the drum circumference, and, for example, within a 90 degree arc. Thus, the operable location of the head blocks **80** can be accommodated within a diameter of the drum. By disposing the head blocks within a dimension substantially equal to the diameter of the drum **160**, the frame **20** width can be reduced to substantially that of the drum diameter.

In various embodiments, each head block **80** generally includes a pair of side plates, a shaft extending between the side plates, accompanying bearings between the plates and the shaft, and a pulley (sheave) connected to the shaft for rotation relative to the side plates. The head block **80** may also include a footing for connecting the head block to the head block mount and hence the frame. It is understood the head blocks **80** may have any of a variety of configurations such as guide surfaces or wheels that permit translation of the cable relative to the head block, and the present lift assembly is not limited to a particular type of construction of the head block.

Drive Mechanism:

The drive mechanism **100** can be operably connected to the drum **160** for rotating the drum and translating the drum along its longitudinal axis, the axis of drum rotation. Referring to FIGS. **4a** and **4b**, the drive mechanism **100** includes a motor **110**, such as an electric motor, and a gearbox **120** for transferring rotational motion of the motor to a drive shaft **114**. The motor **110** may be any of a variety of high torque electric motors such as ac inverter duty motors, dc or servo motors as well as hydraulic motors.

The gearbox **120** can be selected to rotate the drive shaft **114**, and the drum, in a winding (raising) rotation and an unwinding (lowering) rotation. The gearing of the gearbox **120** is at least partially determined by the anticipated loading, the desired lifting rates (speeds) and the motor. A typical gearbox is manufactured by SEW or Emerson.

The drive mechanism **100** may be connected to the frame **20** such that the drive mechanism and the drum **160** translate relative to the frame during rotation of the drum. In some embodiments, the drive mechanism **100** and the frame **20** are sized so that the drive mechanism is enclosed by the frame. Alternatively, the drive mechanism **100** may be connected to a platform that slides outside the frame **20** and thus translates along the axis of rotation with the drum. The choice for connecting the drive mechanism **100** to the frame **20** is at least partially determined the intended operating parameters and manufacturing considerations.

In some constructions, such as those shown in FIGS. **4a** and **4b**, the drive shaft **114** includes a threaded drive portion. The drive portion may be formed by interconnecting a threaded rod to the shaft or forming the shaft with a threaded drive portion. The threaded drive portion is threadingly engaged with a keeper **115**, which in turn is fixedly connected to the frame **20**. The keeper **115** includes a threaded portion or a nut affixed to a plate which receives the threaded portion. That is, referring to FIG. **2**, rotation of the shaft **114** not only rotates the drum **160**, but the drum translates to the left or the

right relative to the frame **20** and hence relative to the attached head blocks. As the drive mechanism **100** is attached to the drum **160** and attached to the frame **20** along a linear slide **111**, the drive mechanism also translates along the axis of drum rotation relative to the frame.

The drive shaft can have any of a variety of cross sections. In some embodiments, a construction of the drive shaft has a faceted cross section such as hexagonal.

Drum:

The drum **160** can be connected to the frame **20** for rotation relative to the frame about the axis of rotation and translation relative to the frame along the axis of rotation. Thus, the drum **160** is rotatable relative to the frame **20** in a winding rotation with accompanying winding translation and an unwinding rotation with accompanying unwinding translation for winding or unwinding a length of cable **14** about a respective winding section.

As shown in FIGS. **1** and **2**, the drum **160** is horizontally mounted and includes the horizontal longitudinal axis of rotation. The drum **160** includes at least one winding section **162**. The winding section **162** is a portion of the drum **160** constructed to receive a winding of the cable **14** for a given drop line. The winding section **162** may include a channeled or contoured surface for receiving the cable. Alternatively, the winding section **162** may be a smooth surface. The number of winding sections **162** corresponds to the number of cables **14** to be controlled by the lift assembly **10**. As shown in FIG. **2**, there are seven winding sections **162** on the shown drum.

Each winding section **162** can be sized to retain a sufficient length of cable **14** to dispose a connected batten **12** between a fully lowered position and a fully raised position. As shown, a single winding of cable **14** is disposed on each winding section **162**. However, it is contemplated that the drum **162** may be controlled to provide multiple layers of winding within a given winding section **162**.

As shown in FIGS. **5-8**, in one configuration of the lift assembly **10**, the drum **160** is a modular construction. The drum **160** is formed of at least one segment **170**. The drum segment **170** defines at least a portion of a winding section **162**. In a first configuration, each drum segment **170** is formed from a pair of mating halves about the longitudinal axis. Each half includes an outer surface defining a portion of the winding section and an internal coupling surface. The internal coupling surface of the drum corresponds to a portion of the cross section of the drive shaft **114**.

When assembled, the drum halves form an outer winding section and the internal coupling surface engages the faceted drive shaft for rotating the drum. Although the internal coupling surface of the drum can have a variety of configurations including slots, detents or teeth, at least one construction employs a faceted drive **114** shaft such a triangular, square, hexagonal, octagonal cross-section.

Referring to FIG. **8** in an alternative modular construction of the drum **160**, the segments **170** are formed of longitudinal lengths **176**, each length being identical and defining a number of windings. In various embodiments, the longitudinal lengths **176** are identical and are assembled by friction fit to form a drum of a desired length. Each segment **170** includes a plurality of tabs **172** and corresponding recesses **174** for engaging additional segments. In this configuration, it has been found advantageous to dispose the longitudinal segments **176** about a substantially rigid core **180** such as an aluminum core as seen in FIG. **6**. The core **180** provides structural rigidity for the segments **176**. In addition, the core **180** does not require extensive manufacturing processes, and can be merely cut to length as necessary.

The modular construction of the drum **160** allows for the ready assembly of a variety of drum lengths. In a first configuration, the drum has an approximate 7-inch diameter with a 0.20 right handed helical pitch. In addition, the drum can be constructed of a plastic such as a thermosetting or thermoplastic material.

The drum **160** includes or is fixedly connected to the drive shaft **114**, wherein the drive shaft is rotatably mounted relative to the frame **20**.

Bias Mechanism:

Although the lift assembly **10** can be employed without requiring counterweights, it is contemplated that a bias mechanism can be employed to reduce the effective load to be raised by the lift assembly. For example, a torsion spring may be disposed between the shaft **114** and the frame **20** such that upon rotation of the shaft in a first direction (generally an unwinding direction), the torsion spring is biased and thus urges rotation of the drum in a winding or lifting rotation. Further, the present lift assembly **10** can be operably connected to an existing counterweight system, wherein the drive mechanism **100** actuates existing counterweights.

Cable Path:

The location of the head blocks **80** on helical head block mount **30**, the drum diameter and the cable sizing can be selected to define a portion of the cable path and particularly a cable take off point. The cable path starts from a winding section **162** on the drum, to a tangential take off point from the winding about the drum **160**. The cable path then extends to the respective head block **80**. The cable path is redirected by the head block **80** to extend horizontally along the length of the frame **20** to a corresponding loft block **220**, wherein the loft block may be internal or external to the frame. Each cable path includes the take-off point and a fleet angle, the angle between the take off point and the respective head block **80**.

As a portion of the cable path for each cable extends parallel to the longitudinal axis of the drum, the take off points for the plurality of winding sections **162** are spaced about the circumference of the drum **160** due to the mounting of the head blocks **80** along the helical head block mount **30**. In a first configuration of FIG. **2**, the seven take off points are disposed within an approximate 90 degree arc of the drum periphery.

In general, an equal length of cable **14** can be disposed about each winding section. The length of the cable paths between the take off point and the end of the frame **20** is different for different cable paths. Thus, a different length of cable **14** may extend from its respective take off point to the end of the frame **20**. However, the lift assembly **10** is constructed so that an equal length of each cable **14** may be operably played from each winding section **162** of the lift assembly **10**.

Load Brake:

The load brake **130** can be located mechanically intermediate the drum **160** and the gearbox **120**, as shown in FIG. **3**. The load brake **130** includes a drive disc **132**, a brake pad **134**, a driven disc **136**, and a peripheral ratchet **138**, a tensioning axle **140** and a tensioning nut **146**.

The drive disc **132** can be connected for rotation with the drive shaft **114** in a one-to-one correspondence. That is, the drive disc **132** can be fixedly attached to the drive shaft **114**. The drive disc **132** can include a concentric threaded coupling **133**. The driven disc **136** can be fixably connected to the drum **160** for rotation with the drum. The driven disc **136** can be fixably connected to the tensioning axle **140**. The tensioning axle **140** can extend from the driven disc **136**. The tensioning axle **140** can include or is fixably connected to a set of braking threads **141** and a spaced set of tensioning threads **143**. The

brake pad 134, friction disc, can be disposed about the tensioning axle 140 intermediate the drive disc 132 and the driven disc 136 and can include the peripheral ratchet 138, which is selectively engaged with a pawl 139.

To assemble the load brake 130, the tensioning axle 140 can be disposed through a corresponding aperture in the gearbox 120 such that the tensioning threads 143 protrude from the gearbox. The braking threads 141 engage the threaded coupling 133 of the drive disc 132. The tensioning nut 146 can be disposed on the tensioning threads 143. The brake pad 134 can thus be disposed between the drive disc 132 and the driven disc 136 to provide a friction surface to each of the discs.

In rotating the motor 110 in a raising or winding direction, the braking threads 141 screw into the corresponding threaded coupler 133 on the drive disc 132, thereby causing the driven disc 136 and the drive disc 132 to compress the brake pad 134. That is, the longitudinal distance between the drive disc 132 and the driven disc 136 decreases. The drive disc 132, the brake pad 134 and the driven disc 136 thus turn as a unit as the cable 14 is wound upon the drum 160.

To lower or unwind cable 14 from the drum 160, the motor 110 and hence drive disc 132 are rotated in the opposite direction. Upon initiation of this direction rotation, the pawl 139 can engage the ratchet 138 to preclude rotation of the brake pad 134. As the drive disc 132 is rotated by the motor 110 in the lowering direction, the braking threads 141 tend to cause the driven disc 136 to move away from the drive disc 132 and hence the brake pad 134, thus allowing the load on the drum 160 to rotate the drum in an unwinding direction. Upon terminating rotation of the drive disc 132 in the lowering direction of rotation, the load on the cable 14 causes the drum 160 and hence driven disc 136 to thread the braking threads 141 further into the coupler 133 against the now fixed braking pad 134 thereby terminating the unwinding rotation of the drum.

The tensioning nut 146 can be used to determine the degree of release of the driven disc 136 from the brake pad 134. The tensioning nut 146 can also be used to accommodate wear in the brake pad 134. The present configuration thus provides a general balance between the motor induced rotation of the drive disc 132 in the unwinding direction and the torque generated by the load on the cable 14 tending to apply a braking force as the driven disc 136 is threaded toward the drive disc 132.

Clip Assembly:

The frame 20 and external loft blocks 220 can be mounted to the building by at least one adjustable clip assembly 40. Each clip assembly 40 can include a J-shaped sleeve 50, a retainer 60 and a J-shaped slider 70. The sleeve 50 and the slider 70 can each have a closed end and a leg. The closed end of the sleeve 50 and the slider 70 can be constructed to engage the flange of a beam, as shown in FIG. 1.

The leg of the sleeve 50 can be sized to slideably receive the retainer 60 and a section of the leg of the slider 70. The sleeve 50 includes a plurality of inwardly projecting teeth 52 at regularly spaced distances along the longitudinal dimension of the leg of the sleeve.

The retainer 60 can be sized to be slideably received within the leg of the sleeve 50. The retainer 60 includes a pair of opposing slots 63 as shown in FIG. 9. A capture bar 62 having corresponding ears 64 can be disposed within the slots 63. The slots 63 in the retainer 60 and the ears 64 of the capture bar 62 are sized to permit the vertical displacement of the capture bar between a lower capture position and a raised release position. The capture bar 62 is sized to engage the teeth 52 of the sleeve 50 in the capture position and be disposed above the teeth in the raised position, whereby the teeth

can pass under the capture bar. The retainer 60 further includes a threaded capture nut 66 fixed relative to the retainer.

The slider 70 can be connected to the retainer 60 by a threaded shaft 72. The threaded shaft 72 is rotatably mounted to the slider 70 and includes an exposed end 76 for selective rotation of the shaft. The rotation of the threaded shaft 72 may be accomplished by a Phillips or regular screw head, a hex-head or any similar structure. The threaded shaft 72, the retainer 60 and the slider 70 are selected to permit the retainer to be spaced from the slider between a maximum distance approximately equal to the distance between adjacent teeth 52 in the sleeve 50, and a minimum distance, where the retainer abuts the slider.

In addition, the sleeve 50 can include an elongate slot 53 extending along the length of the leg having the teeth 52. The slot 53 allows an operator to contact the capture bar 62 and urge the capture bar upward to the raised release position thus allowing the sleeve 50 and the retainer 60/slider 70 to be moved relative to each other and the beam, thereby allowing either release of the clip assembly 40 or readjustment to a different sized beam section. According to at least one construction, the sleeve 50, the retainer 60 and the slider 70 are sized to accommodate the beam flanges having a 4" to a 10" span. The sleeve 50, the retainer 70 and the slider 70 are formed of 1/8" stamped steel.

Control-Power Strip:

As shown in FIG. 2, the present lift assembly also contemplates a control/power strip 90 sized to be disposed between the flanges of a beam. The control strip 90 can include a housing 92 and cabling for supplying electricity power as well as control signals. The housing 92 can provide support to the cabling and can substantially enclose the cabling or merely provide for retention of the cabling. Typically, the control strip 90 includes interconnects at 12 inch centers for engaging a plurality of frames 20. The control strip 90 is attached to the beam by any of a variety of mechanisms including adhesives, threaded fasteners as well as clamps.

Loft Block:

As shown in FIG. 1, the plurality of loft blocks 220 corresponding to the plurality of head blocks 80, can be connected to the building in a spaced relation from the frame 20. The loft blocks 220 are employed to define the portion of the cable path from a generally horizontal path section that extends from the frame 20 to a generally vertical path section that extends to the batten 12 or load. Depending upon the length of the batten 12 and the width of the stage, there may be as few as one or two loft blocks 220 or as many as six, eight, twelve or more.

As shown in FIG. 2, one, two or more internal loft blocks 220 can be located within the frame 20 to allow for cables 14 to pass downward within the footprint of the frame. Thus, the present lift assembly reduces the need for wing space in a building to accommodate counterweight systems.

Typically, at each loft blocks 220, there is a load cable 222 and a passing cable 224, wherein the load cable is the cable redirected by the loft block to extend downward to the batten 12 and the passing cable continues in a generally horizontal direction to the subsequent loft block. In some configurations, the loft blocks 220 accommodate the load cable 222 as well as any passing cables 224.

Referring to FIG. 10, each loft blocks 220 can include a load sheave 230, an optional carrier sheave 240, an upstream guide 250, a downstream guide 260 and a pair of side plates 270. The load sheave 230 can be constructed to engage and track the load cable 222, and the carrier or idler sheave 240 can be constructed for supporting the passing (through) cable

11

224. It is contemplated the load sheave **230** and the carrier sheave **240** may be a single unit having a track for the load cable **222** and separated track or tracks for the passing cables **224**. In some constructions, the carrier sheave **240** is a separate component that engages the load sheave **230** in a friction fit, wherein the load sheave and the carrier sheave rotate together. This construction allows the loft block **220** to be readily constructed with or without the carrier sheave **240** as necessary. Alternatively, the load sheave **230** and the carrier sheave **240** can be separately rotatable members.

The upstream guide **250** can include a through cable inlet **251** and a load cable inlet **253**, wherein the through cable inlet is aligned with the carrier sheave **240** and the load cable inlet is aligned with the load sheave **230**. The upstream guide **250** can be configured to reduce a jumping or grabbing of the cables **14** in their respective sheave assembly. The downstream guide **260** can be located about the exiting path of load cable **220**. Typically, the downstream guide includes a load cable exit aperture **263**.

The side plates can be sized to engage the load and carrier sheaves **230**, **240** as well as the upstream and downstream guides **250**, **260** to form a substantially enclosed housing for the cables **14**. The side plate **270** can include a peripheral channel **273** for engaging and retaining the upstream guide **250** and the downstream guide **260**. The peripheral channels **273** can include an access slot **275** sized to pass the upstream guide **250** and the downstream guide **260** therethrough. In the operating alignment, the peripheral channel **273** can retain the upstream guide **250** and the downstream guide **260**. However, the side plates **270** can be rotated to align the access slot **275** with the upstream guide **250** or the downstream guide **260** so that the guides can be removed from the side plates. The loft block **220** can thereby allows components to be removed without requiring pulling the cables **14** through and subsequent re-cabling.

The loft block **220** can include a shaft about which the load sheave **230**, the carrier sheave **240** (if used), and the side plates **270** are concentrically mounted.

The loft block **220** can engage a coupling bracket **226**, wherein the coupling bracket may be joined to a clip assembly **40** such that the coupling bracket is moved about a pair of orthogonal axis to accommodate tolerances in the building.

Controller:

It is further contemplated the present lift assembly may be employed in connection with a controller **200** for controlling the drive mechanism **100**. Specifically, the controller **200** be a dedicated device or alternatively can include software for running on a personal computer, wherein control signals are generated for the lift assembly **10**.

Stop Sensor:

A proximity sensor or detector **280** can be fixed relative to the load, the batten **12** or the elements connected to the batten **12**. The sensor **280** can be any of a variety of commercially available devices including infra red, ultrasound or proximity sensor. The sensor **280** is operably connectable to the controller by a wire or wireless connection such as infrared. The sensor **280** can be configured to detect an obstacle in the path of the batten **12** moving in either or both the lowering direction or the raising direction. The sensor **280** can provide a signal such that the controller **200** terminates rotation of the motor **110** and hence stops rotation of the drum **160** and movement of the batten **12** upon the sensing of an obstacle.

It is contemplated the sensor **280** may be connected to the batten **12**, wherein the sensor includes an extendable tether **282** sized to locate the sensor **280** on a portion of the load carried by the batten. Thus, the sensor **280** can be operably located with respect to the batten **12** or the load. According to

12

some embodiments, the sensor is sized and colored to reduce visibility by a viewing audience. It is also understood the sensor can be selected to preclude the batten from contacting the deck, floor or stage.

Trim Adjustment:

Referring to FIG. **11** the present lift assembly further provides for a trim adjustment **290**. That is, the relatively fine adjustment of the length of cable in the drop line section of the cable path.

In a first configuration of the trim adjustment **290**, the structure is sized and selected to be disposed within the cross-sectional area of the batten **12**. Thus, the trim adjustment **290** is substantially unobservable to the audience. The trim adjustment can be located within a length of the batten **12**, or form a portion of the batten such as a splice or coupler.

The trim adjustment **290** includes a translator **292** that is rotatably mounted to the batten **12** along its longitudinal dimension and includes a threaded section. The trim adjustment **290** further includes a rider **294** threadedly engaged with the threaded section of the translator **292**, such that upon rotation of the translator, the rider is linearly disposed along the translator.

The cable **14** can be fixedly connected to the rider **294** such that is the rider is translated relative to the batten **12**, additional cable **14** can either drawn into the batten or is passed from the batten.

Rotation of the translator **292** is provided by a user interface **296** such as a socket, hex head or screw interface. Typically, the user interface includes a universal joint **298** such that the interface may be actuated from a non-collinear orientation with the translator.

While the (linear) translator **292** and associated rider **294** are shown in the first configuration, it is understood that a variety of alternative mechanisms may be employed such as ratchets and pawls, pistons, including hydraulic or pneumatic as well as drum systems for taking up and paying out a length of cable **14** within a cross-sectional area of a batten **12** to function as trim adjustment height in a rigging system.

Installation:

The lift assembly **10** can be constructed to accommodate a predetermined number of cables **14**, and hence a corresponding number of winding sections **162** on the drum **160** and head blocks **80**. In addition, upon shipment, the internal loft blocks **220** as well as the external loft blocks **220** can be disposed within the frame **20**. In addition, each cable **14** can be pre-strung so that the cable topologically follows its own cable path.

The hoisting adapters **26** can be threaded with the cable **14** and the separate clip assemblies **40** are connected to a pair of cables from the drum **160**. The cable **14** can be fed from the respective winding section and the clip assemblies are connected to the building. The drum **160** can then rotated to hoist the frame **20** to the installation position. Clip assemblies **40** connected to the frame **20** can be connected to an adjacent beam of the building. The clip assemblies **40** can be engaged with the respective beams and sufficiently tightened to retain the clip relative to the beam. The hoisting clip assemblies on the cables **14** can be removed from the building and the cables, and the hoisting adapter are removed from the frame. The frame **20** can thus be retained relative to the structure.

Upon the frame **20** being attached to the respective beams, the external loft blocks **220** can be removed from the frame and sufficient cable **14** drawn from the drum **160** to locate the loft block adjacent to the respective structural beam. The loft block **220** can then connected to the beam by the clip assembly **40**. The load cable **222** from each loft block **220** can be

13

operably connected to a batten **12** or load. The trim adjustment **290** can then be employed to adjust the relative length of the drop line, as necessary.

As the head blocks **80** longitudinally overlap along the axis of rotation of the drum **160**, the frame **20** can have an approximate 9-11 inch width. Thus, a plurality of frames **20** can be connected to the building in an abutting relation with the drum axis in parallel to provide location on 12-inch centers as seen in FIG. **12**. Alternatively, as shown in FIG. **13**, as the frame **20** can be constructed to include the external loft blocks **220** in any relation to the internal loft blocks, the frames can be staggered along the width of the stage. That is, the second frame is spaced from the first frame in the longitudinal direction such that the ends of the sequential frames are spaced apart.

Operation:

In operation, upon actuation of the motor **110**, the drive shaft **114** and the drum **160** can rotate in the unwind rotation. Such rotation locks the brake pad **134** and threads the driven disc **136** away from the drive disc **132**, which allows cable **14** from each winding section to be paid out from the drum **160** at the respective takeoff point.

The rotation of the shaft **114** which winds or unwinds cable **14** to or from the drum **160** also causes rotation of the threaded portion of the shaft. Rotation of the threaded portion relative to the keeper **115** induces a linear translation of the drum **160** along the axis of drum rotation during winding and unwinding rotation of the drum.

The threading of the threaded portion, the sizing of the drum **160** and the cable **14** are selected such that the fleet angle, or fleet angle limit, is maintained between each head block **80** and the takeoff point of the respective winding section **162**. Thus, by longitudinally translating the drum **160** during unwinding and winding rotation, the fleet angle for each head block **80** and corresponding take off point in the winding section **162** is maintained.

As the fleet angles are automatically maintained, there may be no need for a movable connection between a plurality of head blocks **80** along the helical mount and the frame to maintain a desired fleet angle.

In the bias mechanism configuration, as the drum **160** is rotated with an unwinding rotation, tension is increased in the torsion spring. Thus, upon rotation of the shaft and hence drum in the winding direction, the torsion spring assists in such rotation, thereby reducing the effect of weight of the load such as the batten and any accompanying equipment. This reduction in the effective load allows the sizing of the motor, and gearbox to the adjusted accordingly.

The above Detailed Description includes references to the accompanying drawings, which form a part of the Detailed Description. The drawings show, by way of illustration, specific embodiments in which the invention can be practiced. These embodiments are also referred to herein as "examples." All publications, patents, and patent documents referred to in this document are incorporated by reference herein in their entirety, as though individually incorporated by reference. In the event of inconsistent usages between this document and those documents so incorporated by reference, the usage in the incorporated references should be considered supplementary to that of this document; for irreconcilable inconsistencies, the usage in this document controls.

In this document, the terms "a" or "an" are used, as is common in patent documents, to include one or more than one, independent of any other instances or usages of "at least one" or "one or more." In this document, the term "or" is used

14

to refer to a nonexclusive or, such that "A or B" includes "A but not B," "B but not A," and "A and B," unless otherwise indicated.

In the appended claims, the terms "including" and "in which" are used as the plain-English equivalents of the respective terms "comprising" and "wherein." Also, in the following claims, the terms "including" and "comprising" are open-ended, that is, a system, assembly, device, article, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms "first," "second," and "third," etc. are used merely as labels, and are not intended to impose numerical requirements on their objects.

The above description is intended to be illustrative, and not restrictive. For example, the above-described examples (or one or more features thereof) can be used in combination with each other. Other embodiments can be used, such as by one of ordinary skill in the art upon reviewing the above description. Also, in the above Detailed Description, various features can be grouped together to streamline the disclosure. This should not be interpreted as intending that an unclaimed disclosed feature is essential to any claim. Rather, inventive subject matter can lie in less than all features of a particular disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment. The scope of the invention should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

The Abstract is provided to comply with 3rd C.F.R. §1.72 (b), to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims.

What is claimed is:

1. A lift assembly, comprising:

- a frame connectable to and supportable by one or more spaced overhead beams;
- a drive shaft rotatably connected to the frame about a horizontal axis of rotation;
- a drum connected to the drive shaft, the drum including one or more winding sections for reeling one or more cables connectable to a load;
- one or more head blocks connected to the frame, each head block configured to turn a cable reeled from the one of the one or more winding sections of the drum; and
- a load brake mechanically coupled to a portion of the drum or the drive shaft.

2. The lift assembly of claim 1, wherein each head block is positioned so as to guide the cable along a cable path in the same direction as the axis of rotation of the drive shaft.

3. The lift assembly of claim 1, wherein the drum is translatable relative to the frame along the axis of rotation.

4. The lift assembly of claim 3, wherein translation of the drum maintains a fleet angle between the drum and each head block during raising or lowering of the load.

5. The lift assembly of claim 1, further comprising at least one loft block for engaging the cable.

6. The lift assembly of claim 1, further comprising a loft block spaced from the head block, the head block and the loft block defining a cable path passing from the drum to the head block and then horizontally to the loft block.

7. The lift assembly of claim 1, wherein the load brake includes a drive disc connected to a motor for rotation with the motor, a driven disc connected to the drum for rotation with the drum, and a friction disc located intermediate the drive

15

disc and the driven disc, wherein the drive disc and the driven disc are configured to urge the drive disc and the driven disc against the friction disc in the winding direction of the drum.

8. The lift assembly of claim 1, further comprising a motor connected to the frame, a gearbox connected to the motor, and wherein the load brake is located between the gearbox and the drum.

9. The lift assembly of claim 1, further comprising the one or more cables connectable to the load.

10. A lift assembly, comprising:

a frame connectable to and supportable by one or more spaced beams;

a drum rotatably connected to the frame, via a drive shaft, about an axis of rotation, the drum including one or more winding sections for reeling one or more cables connectable to a load;

one or more head blocks connected to the frame, wherein each head block is located to redirect cables extending from the drum along a cable path in the same direction as the axis of rotation of the drum; and

a load brake mechanically coupled to a portion of the drum or the drive shaft.

11. The lift assembly of claim 10, wherein the drum is translatable relative to the frame along the axis of rotation.

12. The lift assembly of claim 10, further comprising at least one loft block for engaging the cable.

13. The lift assembly of claim 10, further comprising a loft block spaced from the head block, the head block and the loft block further defining the cable path passing from the drum to the head block and then to the loft block.

14. The lift assembly of claim 10, wherein the load brake includes a drive disc connected to a motor for rotation with the motor, a driven disc connected to the drum for rotation with the drum, and a friction disc located intermediate the drive disc and the driven disc, wherein the drive disc and the driven disc are configured to urge the drive disc and the driven disc against the friction disc in the winding direction of the drum.

16

15. The lift assembly of claim 10, further comprising a motor connected to the frame, a gearbox connected to the motor, and wherein the load brake is located between the gearbox and the drum.

16. The lift assembly of claim 10, further comprising the one or more cables connectable to the load.

17. A lift assembly, comprising:

a frame connectable to and supportable by one or more spaced beams;

one or more cables;

a drum rotatably connected to the frame, via a drive shaft, about an axis of rotation, the drum including one or more winding sections for reeling the one or more cables connectable to a load;

one or more head blocks connected to the frame, each head block being fixed relative to the frame for turning one of the one or more cables reeled from the one of the one or more winding sections of the drum;

a loft block spaced from the head block, the head block and the loft block defining a cable path passing from the drum to the head block and then to the loft block, the portion of the cable path between the head block and the loft block being in same direction as the axis of rotation of the drum; and

a load brake mechanically coupled to a portion of the drum or the drive shaft.

18. The lift assembly of claim 17, wherein the drum is translatable relative to the frame along the axis of rotation.

19. The lift assembly of claim 17, wherein the load brake includes a drive disc connected to a motor for rotation with the motor, a driven disc connected to the drum for rotation with the drum, and a friction disc located intermediate the drive disc and the driven disc, wherein the drive disc and the driven disc are configured to urge the drive disc and the driven disc against the friction disc in the winding direction of the drum.

20. The lift assembly of claim 17, further comprising a motor connected to the frame, a gearbox connected to the motor, and wherein the load brake is located between the gearbox and the drum.

* * * * *